



DECLARATION OF PERFORMANCE

No. FLORIM 005

- Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Extruded ceramic tile, with water absorption $6\% < E_b \leq 10\%$
- Intended use(s)
For internal walls
- Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A.,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
- System(s) of assessment and verification of constancy of performance (AVCP)
System 4
- Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 25/06/2013

.....
Place and date of issue


.....
Signature



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE MO ITALY / T. +39 0536 840111 / F. +39 0536 844750
WWW.FLORIM.IT / INFO@FLORIM.IT / CAPITALE SOCIALE EURO 50.000.000 I.V.
ISCR. AL REG. DELLE IMPRESE DELLA C.C.I.A.A. DI MODENA / COD. FISC. E P. IVA IT 01265320364

CE MARKING

Extruded ceramic tiles

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 005	
EN 14411:2012 Extruded ceramic tile, with water absorption $6\% < E_b \leq 10\%$, for internal walls	
Reaction to fire	A1
Bond strength/adhesion, for:	
Cementitious adhesive, type C1	NPD
Durability, for:	
- internal use:	Pass