



**Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata**

No. FLORIM 003

**Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poślizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)**

Rev. 1 del/of/de/vom/de/a 19/01/2015

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka

CERIM

Serie / Series	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA D.M. 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
BLACK & WHITE SLIM/4	N.P.D.	N.P.D.	N.P.D.	N.P.D.
BLACK & WHITE LUX SLIM/4	N.P.D.	N.P.D.	N.P.D.	N.P.D.
I LEGNI NATURALI SLIM/4	N.P.D.	N.P.D.	N.P.D.	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico


VIA CANALETTO 24 / 41042 FIORANO MODENESE MO ITALY / T. +39 0536 840111 / F. +39 0536 844750

WWW.FLORIM.IT / INFO@FLORIM.IT / CAPITALE SOCIALE EURO 50.000.000 I.V.

ISCR. AL REG. DELLE IMPRESE DELLA C.C.I.A.A. DI MODENA / COD. FISC. E P. IVA IT 01265320364

CE MARKING

Fine porcelain stoneware SLIM/4
Coloured body porcelain stoneware SLIM/4
Fine porcelain stoneware MAGNUM

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
09 FLORIM 003	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 700 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass