



Attestation of Conformity

Altaeco S.p.A. via G. Pascoli 4/6 - 20010 Vittuone (MI)

Factory address: S.S. 143 - Cerrione (BI) - Italy
Year in which the CE marking was affixed: 2005
Reference standard: EN 14411
Product classification: Glazed ceramic tiles dust pressed for internal/external floorings
Collection name: Vogue RF
Product reference: Flooring
Product description: all shapes except Flooring40 40x40
Group: BI b (0,5% < E <= 3%)

CHARACTERISTICS

Reaction to fire: A1

Flexural tensile strength:
breaking strength > 1000 N (for tiles with thickness <= 7,5 mm)
breaking strength > 1700 N (for tiles with thickness > 7,5 mm)
modulus of rupture 40 N/mm²

Resistance to thermal shocks: passed

Bond strength/adhesion:
declared value NPD

Slipperiness:
declared value R10 test method DIN 51130
declared value B (A+B) test method DIN 51097
declared value 1) 0,48 test method B.C.R.A. 1) dry (leather)
2) 0,42 test method B.C.R.A. 2) wet (rubber)

Skid resistance:
declared value NPD

Durability - freeze / thaw resistance: passed

Release of dangerous substances:
release of Cadmium NPD mg/dm²
release of Lead NPD mg/dm²